## FORD TRUCKS 3242S HR EURO6

Basic Features				
Vehicle Type	Road Truck			
Axle	8x2			
Emission	Euro 6			
Cabin Type	High Roof Sleeper Cab			
Wheelbase (mm)	5200			
Engine				
Туре	Ecotorq 12,7 litre			
Displacement (cc)	12740			
Diameter x Stroke	130 mm x 160 mm			
Power	420 PS (308,9 kW) / 1800 rpm			
Torque	2150 Nm / 1000-1300 rpm			
Compression Ratio	17 +/- 0,5 : 1			
Oil Filling Volume	50 L			
Coolant Volume	57 L (77 L with Intarder)			
Transmission				
Clutch	430 mm Single Disc			
Automated Transmission / Ratios (1. gear - 16. gear)	Ecotorq 16S 2600 DD AMT (17,03 - 1,00)			
Manuel Transmission / Ratios (1. gear - 16. gear)	ZF 16S 2530 (13,805-0,836)			
Steering				
	Power assisted single circuit			
Chassis				
Chassis Thickness	7 mm with Reinforcement			
Chassis Strength	355 MPa			
Suspension (Front/Rear)	Parabolic Leaf Spring / Compensating Arm Mechanical Suspension			
Axle	Standard Single Reduction			
Axle Ratio	3,08			
Tyres (Front/Rear)	315/80 R 22,5			
Wheel Rim	22,5 x 9 Steel			
Braking System				
Brakes (Front/Rear) (Ø.mm x mm. Length)	430 x 45 Disc Brake			
Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater			
Engine Brake Power	max. 320 kW (Engine Level)			
Intarder Power	max. 450 kW / continuous 160 kW			
Electric System				
Battery	180 Ah			
Alternator / Starter Motor	130 A / 6,5 kW			
Tanks				
Fuel Tank	550 L Aluminium			



Sharing the load

Dimensions (mm)					
Front Overhang			1500		
Wheelbase			5200		
Overall Length			9840		
Distance Between 1st and 2nd Wheel Centers			3770		
Distance Between 2 <sup>nd</sup> and 3 <sup>th</sup> Wheel Centers			1430		
Distance Between 3 <sup>th</sup> and 4 <sup>th</sup> Wheel Centers			1320		
Overall Cab Length			2305		
Overall Vehicle Height			3368		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			866		
Rear Overhang			1820		
Useful Chassis Length			7200		
Chassis height-Front			1049		
Chassis height-Rear			1076		
Ground clearance-Front			305		
Ground clearance-Rear			240		
Turning Radius			10700		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	7100	7100	12000	10400	33000
Kerb Weight	5507	1607	1926	1312	10350
Payload	1593	5493	10074	9088	22650
GVM (legal)	7100	7100	9500	8500	32000

## STANDARD EQUIPMENT

- Air Conditioner
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- Auxiliary Cabin Heater (Dry Type)
- 4 Points Independent Cab Suspension for Day Cab Automated Transmission
- (with Normal Mode, Power Mode, Rocking Mode) Cruise Control
- Engine Brake
- Disc Brake
- Differential Lock
- Electronic Brake System (EBS) and Anti-Lock Brake System (ABS)
- Hill Launch Assist
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlight Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Manually Operated Sunroof Continuous Wear Sensor
- Immobilizer
- Home Safe Light
- Approach Light
- Front and Rear Fog Lamps
- Digital Tachograph
- Spare Wheel
- Tag Axle Lifting (Auto Drop Function)
- Front and Rear Vehicle Antiroll Bars
- Electronic Brake Force Control
- Medium Bumper
- DAB Radio\*\*
- Advanced Driver Assistance Systems (Cybersecurity Improvements, Rear Parking Aid (RPA), Moving-off Information System (MOIS), Blind Spot Information System (BLIS), Tire Pressure Monitoring System (TPMS), Emergency Stop Signal, Alcohol Interlock Facilitation, Intelligent Speed Asistance, Driver Drowsiness Attention Warning, Lane Departure Warning System (LDWS), Advanced Emergency Braking System (AEBS))

## **OPTIONAL EQUIPMENT**

- Cold pack (Includes Dry Type Heater and 225 Ah Battery)
- Cold pack (Includes Wet Type Heater and 225 Ah Battery)
- Cold Pack (Includes Dry Type Heater, Wet Type Heater and 225 Ah Battery)
- Firefighter Pack
- Transmission Driven PTO Options & Interior Control Unit
- Engine Driven PTO & Interior Control Unit
- ADR Pack
- RCV Pack
- Cold Climate Pack
- Auxiliary Cabin Heater (Wet Type)
- Power Cab Tilting
- Metallic Paint / Special Colors
- RHS Free 5900 Wheelbase Option \*
- Rain Sensor (Available with auto light sensor)
- Intarder
- Front Towing Hooks (Double Hook)
- Rear Towing Cross Member
- 8T Front Axle Technical Capacity
- Less Spare Tire
- Technology Pack (High Beam Assist & Pre-Collision Assist) for Pedestrian & iACC with Stop&Go)\*\*\*
- Twin PTO (high ratio) / Twin PTO (low ratio)\*\*\*

\* Available with ADR and 250 L LHS Fuel Tank \*\*DAB Radio can be standard or optional according to the market. \*\*\*Only available with Automated Transmission.

This leaflet includes products designed for Ford vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles Selection of any optional accessories might cause differences from these specifications.